## NSN 5306-01-459-3130

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand **Thread Length:**0.538 inches

**Thread Direction:** 

Fastener Length:

Spline extended washer

**Head Style:** 

**Head Height:** 

Between 1.835 inches and 1.865 inches

За



View Online at https://aerobasegroup.com/nsn/5306-01-459-3130

Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.051 inches and 0.071 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Head Minor Diameter:
Between 0.383 inches and 0.389 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches threads
Special Features:
tensile strength at 900 degrees f
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-459-3130

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0