## NSN 5306-01-459-9111

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-459-9111

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.425 inches  |
| Fastener Length:  |
| Between 1.285 inches and 1.315 inches   |
| Head Style:   |
| Dished hexagon  |
| Head Height:  |
| Between 0.125 inches and 0.145 inches   |
| Width Between Flats:  |
| Between 0.429 inches and 0.439 inches   |
| Locking Feature:  |
| Patch threads   |
| Grip Diameter:  |
| Between 0.2490 inches and 0.2495 inches   |
| Thread Diameter:  |
| 0.250 inches  |
| Grip Length:  |
| Between 0.865 inches and 0.885 inches   |
| Thready Qty Per Inch (tpi):   |
| 28  |
| Min. Tensile Strength (psi):  |
| 160000 pounds per square inch   |
| Minimum Yield Strength:   |
| 95000 pounds per square inch  |
| Material:   |
| Plastic polyamide locking feature   |
| Material Specification:   |
| Ams5371 assn standard single material response fastener or ams 5737 assn standard single material response fastener |
| Surface Treatment:  |
| Passivate fastener  |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response fastener  |
| Thread Series Designator:   |
| Unjf  |
| Specification Data:   |
| 90205-nas6704 professional/industrial association standard  |
| Shelf Life:   |

N/a

## NSN 5306-01-459-9111

Shear Bolt - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A003b0