NSN 5306-01-460-0704

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-460-0704

| Thread Class: |
|--|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.321 inches |
| Fastener Length: |
| Between 0.370 inches and 0.400 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Locking Feature: |
| Patch threads |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.052 inches and 0.072 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205 nas6403 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5306-01-460-0704

Shear Bolt - Page 2 of 2

Fiig: A003b0

