

View Online at <https://aerobasegroup.com/nsn/5306-01-460-4388>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.338 inches

Fastener Length:

5.838 inches

Head Style:

Dished hexagon

Head Height:

Between 0.110 inches and 0.115 inches

Width Between Flats:

0.430 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

End Application:

A-10

Thread Diameter:

0.190 inches

Grip Length:

Between 5.365 inches and 5.385 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Criticality Code Justification:

Feat

Product Name:

Bolt, machine

Special Features:

Used on a-10 shock strut landing gear: altered item made from nas1304-86

Material:

Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response or mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6415 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.