## NSN 5306-01-461-4422

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-461-4422 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 0.892 inches and 0.922 inches **Head Style:** Hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Washer Quantity: **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Primary Washer Outside Diameter:** 0.458 inches **Primary Washer Style:** Finishing **Primary Washer Material Thickness:** 0.064 inches **Special Features:** Furnished with one spacer 5365 01 416 6516 one washer 5310 01 416 8892 and one chan fastener angle 4030 01 344 4411 Material: Steel comp 303se stand-off **Material Specification:** Qq-s-764 cond a federal specification single material response stand-off **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

N/a

Unjf

Shelf Life:

## NSN 5306-01-461-4422

Assembled Washer Bolt - Page 2 of 2



	• -		
In	ıŧ	( )t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5089 spec.