

View Online at <https://aerobasegroup.com/nsn/5306-01-461-4422>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.444 inches and 0.494 inches

Fastener Length:

Between 0.892 inches and 0.922 inches

Head Style:

Hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Washer Quantity:

1

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Primary Washer Outside Diameter:

0.458 inches

Primary Washer Style:

Finishing

Primary Washer Material Thickness:

0.064 inches

Special Features:

Furnished with one spacer 5365 01 416 6516 one washer 5310 01 416 8892 and one chan fastener angle 4030 01 344 4411

Material:

Steel comp 303se stand-off

Material Specification:

Qq-s-764 cond a federal specification single material response stand-off

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5089 spec.