

View Online at <https://aerobasegroup.com/nsn/5306-01-461-4422>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.444 inches and 0.494 inches

**Fastener Length:**

Between 0.892 inches and 0.922 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Washer Quantity:**

1

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Primary Washer Outside Diameter:**

0.458 inches

**Primary Washer Style:**

Finishing

**Primary Washer Material Thickness:**

0.064 inches

**Special Features:**

Furnished with one spacer 5365 01 416 6516 one washer 5310 01 416 8892 and one chan fastener angle 4030 01 344 4411

**Material:**

Steel comp 303se stand-off

**Material Specification:**

Qq-s-764 cond a federal specification single material response stand-off

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5089 spec.