

View Online at <https://aerobasegroup.com/nsn/5306-01-462-2885>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.316 inches

Fastener Length:

Between 1.369 inches and 1.389 inches

Head Style:

Spline drive shear head

Head Height:

0.164 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Head Minor Diameter:

Between 0.448 inches and 0.455 inches

End Application:

F18 e/f

Thread Diameter:

0.250 inches

Grip Length:

1.068 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.261 inches first hole and 1.271 inches first hole

Product Name:

Bolt-close tolerance, spline drive, cre (125 ksi fsu) drilled, short thread

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0