

View Online at <https://aerobasegroup.com/nsn/5306-01-462-3390>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.599 inches

**Fastener Length:**

Between 2.115 inches and 2.135 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.275 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.129 inches first hole and 0.161 inches first hole

**Head Minor Diameter:**

0.707 inches

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 2.709 inches and 2.739 inches

**Thread Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

108000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.882 inches first hole and 2.902 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0