

View Online at <https://aerobasegroup.com/nsn/5306-01-462-3395>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.599 inches

Fastener Length:

Between 2.459 inches and 2.489 inches

Head Style:

Spline drive shear head

Head Height:

0.275 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.129 inches first hole and 0.161 inches first hole

Head Minor Diameter:

0.707 inches

Thread Diameter:

0.437 inches

Grip Length:

Between 1.865 inches and 1.885 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

108000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.882 inches first hole and 2.902 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0