

View Online at <https://aerobasegroup.com/nsn/5306-01-464-3224>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.735 inches

Fastener Length:

Between 1.532 inches and 1.562 inches

Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.4990 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Plastic polyamide locking feature

Material Specification:

Ams5731 assn standard single material response fastener or ams5737 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6308 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0