## NSN 5306-01-464-3864

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-464-3864

## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.583 inches and 0.633 inches Fastener Length: Between 2.281 inches and 2.311 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches Head Minor Diameter: Between 0.448 inches and 0.455 inches **Thread Diameter:** 0.375 inches Grip Length: Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5306-01-464-3864

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

