NSN 5306-01-464-9868

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-464-9868 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.781 inches and 0.797 inches **Fastener Length:** Between 1.453 inches and 1.500 inches **Head Style:** Hexagon **Head Height:** Between 0.265 inches and 0.297 inches Width Between Flats: Between 0.740 inches and 0.752 inches **Hole Diameter:** Between 0.070 inches and 0.080 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.672 inches and 0.703 inches **Hole Quantity:** 1 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon flats Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:**

Passivate

Thread Series Designator:

Unf

NSN 5306-01-464-9868

Machine Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Shelf Life:

Mil-std (military Standard):

Mil-s-18732 spec.

A003b0