NSN 5306-01-466-1020

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-466-1020 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.453 inches **Fastener Length:** Between 3.250 inches and 3.280 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.780 inches and 2.800 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 t y 1 cl3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1108 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-466-1020

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0