NSN 5306-01-467-0619

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-467-0619

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 1.227 inches and 1.277 inches Fastener Length: Between 8.175 inches and 8.205 inches Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches Hole Diameter:
Thread Direction: Right-hand Thread Length: Between 1.227 inches and 1.277 inches Fastener Length: Between 8.175 inches and 8.205 inches Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Right-hand Thread Length: Between 1.227 inches and 1.277 inches Fastener Length: Between 8.175 inches and 8.205 inches Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Thread Length: Between 1.227 inches and 1.277 inches Fastener Length: Between 8.175 inches and 8.205 inches Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Between 1.227 inches and 1.277 inches Fastener Length: Between 8.175 inches and 8.205 inches Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Fastener Length: Between 8.175 inches and 8.205 inches Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Between 8.175 inches and 8.205 inches Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Head Style: Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Dished hexagon Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Head Height: Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches
Width Between Flats: Between 0.928 inches and 0.940 inches
Between 0.928 inches and 0.940 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.6235 inches and 0.6240 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 6.928 inches and 6.948 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon flats
Surface Finish:
32.0 microinches threads
Material:
waterial.
Titanium alloy uns r56400
Titanium alloy uns r56400
Titanium alloy uns r56400 Material Specification:
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response

80205-nas6410 professional/industrial association standard

NSN 5306-01-467-0619

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0