NSN 5306-01-467-3613

Shear Bolt - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.707 inches

Fastener Length:

Between 1.630 inches and 1.660 inches

Head Style:

Spline extended washer

Head Height:

Between 0.327 inches and 0.347 inches

Extended Washer Diameter:

Between 0.691 inches and 0.701 inches

Extended Washer Thickness:

Between 0.044 inches and 0.064 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Head Minor Diameter:

0.448 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.928 inches and 0.948 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

260000 pounds per square inch

Material:

Cobalt comp mp-35-n or cobalt alloy mp-159

Material Specification:

Ams 5844 assn standard 1st material response and ams 5842 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5306-01-467-3613

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

