## NSN 5306-01-467-4320

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-467-4320 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** 4.700 inches **Head Style:** Hexagon extended washer **Head Height:** 1.500 inches Width Between Flats: 0.875 inches **Extended Washer Diameter:** 1.310 inches **Extended Washer Thickness:** 0.640 inches **Point Length:** 0.200 inches **Point Diameter:** Between 0.700 inches and 0.720 inches First Diameter From Head: Between 0.740 inches and 0.750 inches Point Style: Full dog **End Application:** 5840-01-412-9653 **Thread Diameter:** 0.875 inches Thready Qty Per Inch (tpi): Hardness Rating: 35.0 rockwell c and 42.0 rockwell c **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 90.0 degrees Material: Steel comp 630 **Material Specification:** 

Mil-c-24111, cond 2 military specification single material response

## NSN 5306-01-467-4320

Mil-c-24111 spec.

Externally Relieved Body Bolt - Page 2 of 2



Surface Treatment:
Lubricant
Surface Treatment Specification:
Mil-l-46010, type ii military specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):