

View Online at <https://aerobasegroup.com/nsn/5306-01-467-6202>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.763 inches

Fastener Length:

Between 2.223 inches and 2.253 inches

Head Style:

Spline extended washer

Head Height:

Between 0.383 inches and 0.403 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.057 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Head Minor Diameter:

Between 0.485 inches and 0.500 inches

End Application:

Harrier adaptor pylon

Thread Diameter:

0.437 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Special Features:

Undrilled head; cadmium plated

Material:

Nickel alloy 718

Material Specification:

Ams 566 assn standard single material response or ams 5663 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

96906-ms14181 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0