NSN 5306-01-467-6202

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-467-6202

| Inread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.763 inches |
| Fastener Length: |
| Between 2.223 inches and 2.253 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| Between 0.383 inches and 0.403 inches |
| Extended Washer Diameter: |
| Between 0.807 inches and 0.817 inches |
| Extended Washer Thickness: |
| Between 0.053 inches and 0.057 inches |
| Grip Diameter: |
| Between 0.4360 inches and 0.4370 inches |
| Head Minor Diameter: |
| Between 0.485 inches and 0.500 inches |
| End Application: |
| Harrier adaptor pylon |
| Thread Diameter: |
| 0.437 inches |
| Grip Length: |
| Between 1.615 inches and 1.635 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Special Features: |
| Undrilled head; cadmium plated |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 566 assn standard single material response or ams 5663 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| |

NSN 5306-01-467-6202

Shear Bolt - Page 2 of 2



| Spec | ific | ation | Data: |
|------|------|-------|-------|
|------|------|-------|-------|

96906-ms14181 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0