

View Online at <https://aerobasegroup.com/nsn/5306-01-467-9403>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.828 inches

**Fastener Length:**

0.828 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.547 inches and 0.567 inches

**Width Between Flats:**

Between 0.616 inches and 0.627 inches

**Extended Washer Diameter:**

Between 0.928 inches and 0.938 inches

**Extended Washer Thickness:**

Between 0.123 inches and 0.143 inches

**Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

**Thread Diameter:**

0.562 inches

**Grip Length:**

1.250 inches

**Nonstandard Thread Pitch Diameter:**

+0.5354/+0.5359 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Thread Pitch In Millimeters:**

13.3

**External Thread Tolerance Class:**

2a

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard 1st material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, typeii, class2 federal specification 1st treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0