

View Online at <https://aerobasegroup.com/nsn/5306-01-468-2932>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.403 inches

**Fastener Length:**

0.403 inches

**Head Style:**

Flush

**Head Diameter:**

0.50663 inches

**Head Height:**

0.1110 inches

**Grip Diameter:**

0.249 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.187 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

5790 pounds per square inch

**Thread Pitch In Millimeters:**

0.9

**External Thread Tolerance Class:**

3a

**Material:**

Steel comp 4130 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Passivate or cadmium

**Surface Treatment Specification:**

Qq-p-35 federal specification 1st treatment response or qq-p-416, typeii, class2 federal specification 1st treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.