NSN 5306-01-468-2932



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-468-2932 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** 0.403 inches **Head Style:** Flush **Head Diameter:** 0.50663 inches **Head Height:** 0.1110 inches **Grip Diameter:** 0.249 inches **Thread Diameter:** 0.250 inches **Grip Length:** 0.187 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5790 pounds per square inch **Thread Pitch In Millimeters:** 0.9 **External Thread Tolerance Class:** За Material: Steel comp 4130 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-6049 military specification 4th material response **Surface Treatment:** Passivate or cadmium **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response or qq-p-416, typeii, class2 federal specification 1st treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5306-01-468-2932

Close Tolerance Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.