# NSN 5306-01-468-2932

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-468-2932

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.403 inches

## Fastener Length:

0.403 inches

#### Head Style:

Flush

#### Head Diameter:

0.50663 inches

#### **Head Height:**

0.1110 inches

#### **Grip Diameter:**

#### 0.249 inches

Thread Diameter:

0.250 inches

## Grip Length:

0.187 inches

# Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

5790 pounds per square inch

## **Thread Pitch In Millimeters:**

0.9

## **External Thread Tolerance Class:**

3a

## Material:

Steel comp 4130 or steel comp 4340 or steel comp 8740

## **Material Specification:**

Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification

3rd material response or mil-s-6049 military specification 4th material response

#### Surface Treatment:

Passivate or cadmium

## Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response or qq-p-416, typeii, class2 federal specification 1st treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5306-01-468-2932

Close Tolerance Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

