

View Online at <https://aerobasegroup.com/nsn/5306-01-468-2932>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.403 inches

Fastener Length:

0.403 inches

Head Style:

Flush

Head Diameter:

0.50663 inches

Head Height:

0.1110 inches

Grip Diameter:

0.249 inches

Thread Diameter:

0.250 inches

Grip Length:

0.187 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

5790 pounds per square inch

Thread Pitch In Millimeters:

0.9

External Thread Tolerance Class:

3a

Material:

Steel comp 4130 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Passivate or cadmium

Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response or qq-p-416, typeii, class2 federal specification 1st treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.