NSN 5306-01-468-4884

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-468-4884 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 2.680 inches **Fastener Length:** 3.340 inches **Head Style:** Hexagon extended washer **Head Height:** 0.590 inches Width Between Flats: 0.750 inches **Extended Washer Diameter:** 1.120 inches **Extended Washer Thickness:** 0.190 inches **Shank Unthreaded Hole Diameter:** 0.125 inches first hole and 0.129 inches first hole First Diameter From Head: 0.500 inches **Second Diameter From Head:** 0.380 inches **End Application:** 2350-01-368-9528 **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 13 Hardness Rating: 33.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 3.620 inches first hole **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 **Material Specification:** Astm a829 assn standard single material response or astm a332 assn standard single material response or astm a331 assn standard single

Surface Treatment: Zinc

material response

NSN 5306-01-468-4884

Externally Relieved Body Bolt - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Astm b633, type ii, sc2 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0