

View Online at <https://aerobasegroup.com/nsn/5306-01-468-5167>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.468 inches

**Fastener Length:**

Between 1.953 inches and 1.983 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.290 inches and 0.310 inches

**Width Between Flats:**

0.371 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.438 inches

**Extended Washer Thickness:**

Between 0.059 inches and 0.079 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**End Application:**

F-15i

**Thread Diameter:**

0.250 inches

**Grip Length:**

1.500 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Product Name:**

Bolt, close toler

**Material:**

Steel comp xm-13

**Material Specification:**

23-112 type a mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0