

View Online at <https://aerobasegroup.com/nsn/5306-01-468-5280>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 0.678 inches and 0.698 inches

Head Style:

Spline drive shear head

Head Height:

0.187 inches

Grip Diameter:

Between 0.484 inches and 0.511 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Head Minor Diameter:

Between 0.514 inches and 0.521 inches

End Application:

Used on f18 e&f

Thread Diameter:

0.312 inches

Grip Length:

0.313 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.570 inches first hole and 0.580 inches first hole

Product Name:

Bolt-close tolerance, spline drive, cres (125 ksi fsu) drilled, short thread

Material:

Steel comp xm-13

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0