

View Online at <https://aerobasegroup.com/nsn/5306-01-470-5269>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.037 inches

Fastener Length:

Between 4.047 inches and 4.077 inches

Head Style:

Bevel-conical

Head Diameter:

Between 1.220 inches and 1.230 inches

Head Height:

0.750 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.750 inches

Width Across Flats:

Between 0.5630 inches and 0.5660 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or il-s-8503 military specification 10th material response or i-s-6098 military specification 10th material response or il-s-6049 military specification 10th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

96906-20012 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.