## NSN 5306-01-470-7838

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-470-7838

<b>T</b> I I	01
Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

0.454 inches

#### Fastener Length:

Between 2.939 inches and 2.969 inches

#### **Head Style:**

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

#### Width Between Flats:

Between 0.554 inches and 0.564 inches

#### Grip Diameter:

Between 0.373 inches and 0.374 inches

#### Thread Diameter:

0.375 inches

#### Grip Length:

Between 2.490 inches and 2.510 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Minimum Yield Strength:

95000 pounds per square inch

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### **Surface Treatment Specification:**

Qq-p-461, type 2 cl 2 federal specification single treatment response

### Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas6306 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5306-01-470-7838

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

