

View Online at <https://aerobasegroup.com/nsn/5306-01-471-5557>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.497 inches

Fastener Length:

Between 1.606 inches and 1.653 inches

Head Style:

Double hexagon

Head Height:

Between 0.200 inches and 0.220 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.101 inches first hole and 0.111 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

1.125 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.441 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0