

View Online at <https://aerobasegroup.com/nsn/5306-01-471-5557>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.497 inches

**Fastener Length:**

Between 1.606 inches and 1.653 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.200 inches and 0.220 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.101 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.125 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.441 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0