## NSN 5306-01-471-5557



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-471-5557 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.497 inches **Fastener Length:** Between 1.606 inches and 1.653 inches **Head Style:** Double hexagon **Head Height:** Between 0.200 inches and 0.220 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.101 inches first hole and 0.111 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** 1.125 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.441 inches first hole Surface Finish: 32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Ams-qq-p-35 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-01-471-5557

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0