

View Online at <https://aerobasegroup.com/nsn/5306-01-472-3594>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.330 inches and 0.430 inches

**Fastener Length:**

Between 1.940 inches and 1.960 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.261 inches and 0.301 inches

**Width Between Flats:**

Between 1.053 inches and 1.073 inches

**Hole Diameter:**

0.070 inches

**First Diameter From Head:**

Between 0.7476 inches and 0.7585 inches

**Second Diameter From Head:**

Between 0.410 inches and 0.430 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

1.470 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.570 inches

**End Application:**

Chinook ch-47

**Thread Diameter:**

0.500 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Hole Configuration Style:**

Hexagon corners

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.