## NSN 5306-01-472-5446

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-472-5446 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.659 inches **Fastener Length:** Between 2.044 inches and 2.074 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Head Minor Diameter:** Between 0.423 inches and 0.438 inches **End Application:** F/a-18e aircraft **Thread Diameter:** 0.3750 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Criticality Code Justification:** Agav **Surface Finish:** 32.0 microinches bearing surface of head Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response or ams 5663 assn standard single material response **Surface Treatment:** Cadmium

Unjf

**Thread Series Designator:** 

## NSN 5306-01-472-5446

Shear Bolt - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0