NSN 5306-01-473-6241

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-473-6241

Thread Direction: Right-hand Thread Length: 0.589 inches Fastener Length: Between 1.099 inches and 1.129 inches Head Style: Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24
Right-hand Thread Length: 0.589 inches Fastener Length: Between 1.099 inches and 1.129 inches Head Style: Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Thread Length: 0.589 inches Fastener Length: Between 1.099 inches and 1.129 inches Head Style: Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
0.589 inches Fastener Length: Between 1.099 inches and 1.129 inches Head Style: Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Fastener Length: Between 1.099 inches and 1.129 inches Head Style: Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Between 1.099 inches and 1.129 inches Head Style: Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Head Style: Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Spline extended washer Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Head Height: Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Between 0.302 inches and 0.322 inches Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Extended Washer Diameter: Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Between 0.575 inches and 0.585 inches Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Extended Washer Thickness: Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Between 0.035 inches and 0.055 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Grip Diameter: Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Between 0.3110 inches and 0.3120 inches Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Head Minor Diameter: Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Between 0.360 inches and 0.375 inches End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
End Application: F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
F/a-18e aircraft Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi):
Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24
Thready Qty Per Inch (tpi): 24
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Criticality Code Justification:
Agav
Surface Finish:
32.0 microinches bearing surface of head
Material:
Nickel alloy 718
·
Material Specification:
Material Specification:
Material Specification: Ams 5662 assn standard single material response or ams 5663 assn standard single material response
Material Specification: Ams 5662 assn standard single material response or ams 5663 assn standard single material response Surface Treatment:

NSN 5306-01-473-6241

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0