NSN 5306-01-473-6398

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-473-6398

Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.838 inches **Fastener Length:** Between 2.973 inches and 3.003 inches **Head Style:** Spline extended washer **Head Height:** Between 0.440 inches and 0.460 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Head Minor Diameter:** Between 0.547 inches and 0.562 inches **End Application:** F/a-18e aircraft **Thread Diameter:** 0.5000 inches **Grip Length:** Between 2.115 inches and 2.135 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Criticality Code Justification:** Agav **Surface Finish:** 32.0 microinches bearing surface of head Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response or ams 5663 assn standard single material response **Surface Treatment:**

Surrace Treatmen

Thread Series Designator:

Unjf

Cadmium

NSN 5306-01-473-6398

Shear Bolt - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0