## NSN 5306-01-474-1008

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-474-1008

Thread Class:
3a Thread Directions
Thread Direction:
Right-hand
Thread Length:
0.589 inches
Fastener Length:
Between 1.599 inches and 1.629 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.360 inches and 0.375 inches
End Application:
F/a-18e aircraft
Thread Diameter:
0.3125 inches
Grip Length:
Between 0.990 inches and 1.010 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Criticality Code Justification:
Agav
Surface Finish:
32.0 microinches bearing surface of head
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
11-14

Unjf

## NSN 5306-01-474-1008

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

