NSN 5306-01-474-1089

Shear Bolt - Page 1 of 2

Unjf



View Online at https://aerobasegroup.com/nsn/5306-01-474-1089

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.495 inches
Fastener Length:
Between 1.130 inches and 1.160 inches
Head Style:
Spline extended washer
Head Height:
Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.026 inches and 0.046 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Head Minor Diameter:
Between 0.235 inches and 0.250 inches
End Application:
F/a-18e aircraft
Thread Diameter:
0.250 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Criticality Code Justification:
Agav
Surface Finish:
32.0 microinches bearing surface of head
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
- Linif

NSN 5306-01-474-1089

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

