## NSN 5306-01-474-1090

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-474-1090 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.589 inches **Fastener Length:** Between 1.599 inches and 1.629 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.035 inches and 0.055 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Head Minor Diameter:** Between 0.360 inches and 0.375 inches **End Application:** F/a-18e aircraft **Thread Diameter:** 0.3125 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Criticality Code Justification:** 

Agav

**Surface Finish:** 

32.0 microinches bearing surface of head

Material:

Nickel alloy 718

**Material Specification:** 

Ams 5662 assn standard single material response or ams 5663 assn standard single material response

**Surface Treatment:** 

Cadmium

**Thread Series Designator:** 

Unjf

## NSN 5306-01-474-1090

Shear Bolt - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0