## NSN 5306-01-474-5840

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-474-5840

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
|  |
| Right-hand Thread Length:  |
| Thread Length: 0.589 inches  |
|  |
| Fastener Length:  Between 1.474 inches and 1.504 inches  |
|  |
| Head Style:  |
| Spline extended washer   |
| Head Height:  Between 0.302 inches and 0.322 inches  |
| Extended Washer Diameter:  |
| Between 0.575 inches and 0.585 inches  |
| Extended Washer Thickness:   |
|  |
| Between 0.035 inches and 0.055 inches  |
| Grip Diameter:  Between 0.3110 inches and 0.3120 inches  |
| Head Minor Diameter:   |
| Between 0.360 inches and 0.375 inches  |
|  |
| End Application:   |
| F/a-18e aircraft Thread Diameter:  |
|  |
| 0.3125 inches  |
| Grip Length:   |
| Between 0.865 inches and 0.885 inches  |
| Thready Qty Per Inch (tpi):  |
| 24 Min. Tongila Strangth (ppi)   |
| Min. Tensile Strength (psi):   |
| 220000 pounds per square inch  |
| Criticality Code Justification:  |
| Agav   |
| Surface Finish:  |
| 32.0 microinches bearing surface of head   |
| Material:  |
| Nickel alloy 718   |
| Material Specification:  |
| Ams 5662 assn standard single material response or ams 5663 assn standard single material response |
| Surface Treatment:   |
| Cadmium  |
| Thread Series Designator:  |
| Unjf   |

## NSN 5306-01-474-5840

Shear Bolt - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0