## NSN 5306-01-475-3169

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-475-3169 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.763 inches **Fastener Length:** Between 1.273 inches and 1.303 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Head Minor Diameter:** Between 0.485 inches and 0.500 inches **End Application:** F/a-18e aircraft **Thread Diameter:** 0.4375 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Criticality Code Justification:** Agav **Surface Finish:** 32.0 microinches bearing surface of head Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response or ams 5663 assn standard single material response **Surface Treatment:** Cadmium

**Thread Series Designator:** 

Unjf

## NSN 5306-01-475-3169

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0