## NSN 5306-01-476-7799

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-476-7799 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.453 inches **Fastener Length:** Between 2.759 inches and 2.799 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.204 inches Width Between Flats: Between 0.490 inches and 0.502 inches **Shoulder Diameter:** 0.309 inches first shoulder and 0.312 inches first shoulder **Shoulder Length:** 1.072 inches first shoulder and 1.092 inches first shoulder **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 4080 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6050 military specification single material response or mil-s-6098 military specification single material response or mil-s-6758 military specification single material response or ams6300 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-476-7799

Shoulder Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.