## NSN 5306-01-477-5582



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-477-5582 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.467 inches **Fastener Length:** Between 1.358 inches and 1.373 inches **Head Style:** Spline drive shear head **Head Height:** 0.187 inches **Hole Diameter:** Between 0.065 inches and 0.075 inches **Grip Diameter:** Between 0.484 inches and 0.511 inches **Head Minor Diameter:** Between 0.595 inches and 0.605 inches **End Application:** F18 e/f **Thread Diameter:** 0.313 inches **Grip Length:** Between 0.865 inches and 0.885 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Hole Configuration Style:** Round **Criticality Code Justification:** Agav **Product Name:** Bolt, close tolerance, spline drive, cres (125 ksi fsu) Material:

Steel comp xm-13

**Material Specification:** 

Ams 5629 assn standard single material response

## NSN 5306-01-477-5582

Close Tolerance Bolt - Page 2 of 2



| Surface Treatment:                               |
|--|
| Passivate  |
| Surface Treatment Specification:                 |
| Ams 5629 assn standard single treatment response |
| Thread Series Designator:                        |
| Unjf   |
| Shelf Life:                                      |
| N/a  |
| Unit Of Measure:                                 |
|  |
| Demilitarization:                                |
| No   |
| Fiig:  |

A003b0