

View Online at <https://aerobasegroup.com/nsn/5306-01-477-5786>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.276 inches

Fastener Length:

Between 0.8285 inches and 0.8485 inches

Head Style:

Spline drive shear head

Head Height:

0.140 inches

Grip Diameter:

Between 0.359 inches and 0.380 inches

Shank Unthreaded Hole Diameter:

0.070 inches fastener and 0.075 inches fastener

Head Minor Diameter:

Between 0.383 inches and 0.389 inches

End Application:

F18 e/f

Thread Diameter:

0.190 inches

Grip Length:

0.563 inches

Thready Qty Per Inch (tpi):

32

Criticality Code Justification:

Agav

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.966 inches fastener and 0.986 inches fastener

Product Name:

Bolt-close tolerance, spline drive, cres (125 ksi fsu) drilled, short thread

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0