

View Online at <https://aerobasegroup.com/nsn/5306-01-477-5792>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.453 inches

**Fastener Length:**

Between 2.068 inches and 2.088 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.257 inches

**Grip Diameter:**

Between 0.671 inches and 0.703 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Head Minor Diameter:**

Between 0.711 inches and 0.717 inches

**End Application:**

F18 e/f

**Thread Diameter:**

0.4375 inches

**Grip Length:**

1.625 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.953 inches first hole and 1.963 inches first hole

**Product Name:**

Bolt-close tolerance, spline drive, cres (125 ksi fsu) drilled, short thread

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0