## NSN 5306-01-478-3506

Shear Bolt - Page 1 of 2



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.538 inches Fastener Length: Between 1.153 inches and 1.173 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.051 inches and 0.071 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches Head Minor Diameter: Between 0.383 inches and 0.389 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a



## NSN 5306-01-478-3506

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

