## NSN 5306-01-479-7676

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-479-7676

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.531 inches
Fastener Length:
1.406 inches
Head Style:
Hexagon
Head Height:
Between 0.172 inches and 0.204 inches
Width Between Flats:
Between 0.490 inches and 0.502 inches
Grip Diameter:
Between 0.309 inches and 0.312 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Material:
Steel comp 4037 or steel comp 8630 or steel comp 8740 or steel comp 4140 or steel comp 8735 or steel comp 4130
Material Specification:
Ams 6300 assn standard 1st material response or ams 6280 assn standard 2nd material response or mil-s-6050 military specification 2nd
material response or ams6322 assn standard 3rd material response or mil-s-6049 military specification 3rd material response or ams 6382
assn standard 4th material response or mil-s-6098 military specification 5th material response or mil-s-6758 military specification all
material responses
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, ty ii, cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

## NSN 5306-01-479-7676

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.