

View Online at <https://aerobasegroup.com/nsn/5306-01-479-8224>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.578 inches

**Fastener Length:**

Between 1.625 inches and 1.655 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.052 inches and 1.072 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.443 inches first hole

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Chromium plate per qq-c-320, class 2 on shank only, all other surfaces cadmium plated

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response and ams5737 assn standard single material response and ams5853 assn standard single material response

**Surface Treatment:**

Chromium

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6706 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0