## NSN 5306-01-480-4899

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-480-4899

Thr	read Class:
3a	
Thr	read Direction:
Rig	ht-hand
Thr	ead Length:
0.6	660 inches
Fas	stener Length:
Bet	ween 2.339 inches and 2.369 inches
Hea	ad Style:
Hex	kagon
Hea	ad Height:
Bet	ween 0.375 inches and 0.390 inches
Wio	Ith Between Flats:
Bet	ween 1.052 inches and 1.065 inches
Gri	p Diameter:
Bet	ween 0.7440 inches and 0.7445 inches
Thr	ead Diameter:
0.7	50 inches
Gri	p Length:
Bet	ween 1.678 inches and 1.698 inches
Ho	e Quantity:
1	
Ho	е Туре:
Dril	led
Thr	eady Qty Per Inch (tpi):
16	
Pro	duct Name:
Nav	<i>y</i> special project
Spe	ecial Features:
Dril	led shank
Ma	terial:
Iror	alloy 660
Ma	terial Specification:
Am	s5731, ams5732, ams5737 assn standard 1st material response or ams5853 assn standard 2nd material response
Su	face Treatment:
Pas	ssivate
Su	face Treatment Specification:
Nas	s4003 assn standard 1st treatment response
Thr	ead Series Designator:
Unj	f
Spe	ecification Data:
802	05-nas6303-6320 professional/industrial association standard

## NSN 5306-01-480-4899

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

