

View Online at <https://aerobasegroup.com/nsn/5306-01-480-6410>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.614 inches

Fastener Length:

Between 0.849 inches and 0.879 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

0.439 inches

Extended Washer Diameter:

Between 0.629 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Hole Diameter:

Between 0.106 inches and 0.111 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

End Application:

F18 e/f

Thread Diameter:

0.375 inches

Grip Length:

0.250 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Double hexagon flats

Criticality Code Justification:

Agav

Product Name:

Bolt-close tolerance, 12 point, flange head, 220 ksi ftu, cres

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0